

# Port Sections Guide

## Port of Rotterdam




29-9-2011

<b>Section</b>	<b>Waalhaven</b>
<b>Check</b>	<b>Check Maasmond, Nieuwe Waterweg &amp; Nieuwe Maas</b>
<b>Photo/Chart</b>	<b>64, 67, 68 &amp; 69</b>

<b>Position (lat / lon)</b>	51°53'.6N 004°26'.5E
<b>UKC policy alongside</b>	Always afloat, UKC recommended 0,30 meter static.
<b>Tidal range</b>	Mean range: 1.80m
<b>Range of water densities</b>	Mean: 998 kg/m <sup>3</sup> , Min: 997 kg/m <sup>3</sup> , Max: 998 kg/m <sup>3</sup>
<b>Bottom type</b>	Mix of mud and silt. Mix rate depends on tidal situation.
<b>Dredging regime</b>	The fairway and berth depths are monitored by regular soundings and maintained by dredging when necessary. Maintained by Rotterdam Port Authority.
<b>Free text</b>	N/A

<b>Manoeuvre</b>	<b>Arrival</b>
------------------	----------------

<b>UKC policy</b>	UKC = 0,50 meter static.
<b>Size restriction</b>	L max 310 meter.
<b>Tidal restriction</b>	<p><b>Bulkcarriers, L ≥ 200 m. and / or T ≥ 11.0 m:</b>  HW R'dam -3.15 till HW R'dam -1.45 and HW R'dam + 0.30 till HW R'dam +2.00.  max high tide 0,8 kn max low tide 0,7 kn.</p> <p><b>Vessels other than bulkcarriers L ≥ 230 m and &lt; 290 meter and T ≥ 11.0 m:</b>  T &lt; 11.0 m: HWR till HWR -1.15  T ≥ 11.0 m and &lt; 12.2 m: HWR till HWR -1.15  max high tide 1,1 kn.  Attention: from HWR +2.00 till HWR -3.15 with tugs, one tug BP ≥ 45 T, max eb current 2 knots.  T ≥ 12.2 m and &lt; 13.0 m: HWR till HWR -1.45  Attention: from HWR +2.00 till HWR -3.15 with tugs, one tug BP ≥ 45 T, max eb current 1,5 knots  max high tide 1,1 kn max low tide 2,0 kn.  T ≥ 13.0 m: HWR -4.45 till HWR -1.45 and HWR +0.30 till HWR +3.00  Attention: from HWR -4.45 till HWR -3.15 and HWR +2.00 till HWR +3.00 with tugs,  one tug BP ≥ 45 T, max eb current 1 knots.  max high tide 1,1 kn max low tide 1,5 kn.</p> <p><b>Vessels other than bulkcarriers L ≥ 290- m:</b>  T &lt; 11.0 m: HWR till HWR -1.45, with tugs, one tug BP ≥ 45 T, max eb current 1,5 knots  max high tide 1,1 kn max low tide 1,5 kn.  T ≥ 11.0 m and &lt; 13.0 m: HWR +0.30 till HWR +3.00 and HWR -4.45 till HWR -1.45 with tugs,  one tug BP ≥ 45 T, max eb current 1 knots.  max high tide 0,7 kn max low tide 1,0 kn.  T ≥ 13,0 m: HWR -3.15 till HWR -1.45 and HWSR +0.30 till HWR +2.00 with tugs,  one tug BP ≥ 45 T.</p>
<b>Wind restriction</b>	N/A
<b>Visibility restriction</b>	N/A
<b>Speed restriction</b>	Maximum 5 - 6 knots on the river if UKC < 10%.
<b>Passing requirements</b>	Minimum passing distance between pier 6 and 7 100 meters at all times.
<b>Tug use</b>	L ≥ 230 meter must use tugs with BP ≥ 27 tons. L ≥ 290 meter must use tugs, at least one tug with BP ≥ 45 tons. Number of tugs to be determined by pilot. Rendezvous point close to 51°53.7'N, 004°20.0'E



# Port Sections Guide

## Port of Rotterdam



29-9-2011

<b>Section</b>	<b>Waalhaven</b>
<b>Check</b>	<b>Check Maasmond, Nieuwe Waterweg &amp; Nieuwe Maas</b>
<b>Photo/Chart</b>	<b>64, 67, 68 &amp; 69</b>

<b>Berthing requirements</b>	N/A
<b>Free text option</b>	Vessels larger than 220 meter might be escorted at the basin entrance and at the south side of the basin.

<b>Manoeuvre</b>	<b>Departure</b>
<b>UKC policy</b>	See arrival
<b>Size restriction</b>	N/A
<b>Tidal restriction</b>	<b>L ≥ 230 m and &lt; 290 meter:</b> T < 11.0 m: HWR till HWR -1.45 max high tide 1,1 kn. Attention: from HWR till HWR +0.30 with tugs, one tug BP ≥ 45 T. T ≥ 11.0 m and < 13.0m: HWR till HWR -1.45 max high tide 1,1 kn max low tide 1,5 kn. Attention: from HWR till HWR +0.30 with tugs, one tug BP ≥ 45 T and from HWR +3.00 till HWR - 5.45 with tugs, one tug BP ≥ 45 T, max eb current 1,5 knots. T ≥ 13.0 m: HWR -2.45 till HWR -1.45 and HWR +0.30 till HWR +1.30, with tugs, one tug BP ≥ 45 T max high tide 0,8 kn max low tide 0,5 kn. <b>L ≥ 290 meter:</b> T < 11.0: HWR till HWR -1.45, with tugs, one tug BP ≥ 45 T. max high tide 1,1 kn. T ≥ 11.0 and < 13.0 m: HWR till HWR -1.45, with tugs, one tug BP ≥ 45 T. max high tide 1,1 kn max low tide 1,5 kn. Attention: from HWR +3.00 till HWR -5.45 max eb current 1,5 knots. T ≥ 13.0 m: HWR -2.45 till HWR -1.45 and HWR +0.30 till HWR + 1.30, with tugs, one tug BP ≥ 45 T.
<b>Wind restriction</b>	N/A
<b>Visibility restriction</b>	N/A
<b>Speed restriction</b>	N/A
<b>Passing requirements</b>	See arrival
<b>Tug use</b>	<b>L ≥ 290 meter</b> must use tugs, at least one tug with BP ≥ 45 tons. One tug or 45 ton BP can be replaced by one conventional tug with min. 25 T BP and 1 VS, ASD or tractor tug of min. 30 T.
<b>Unberthing requirements</b>	N/A
<b>Free text option</b>	N/A